

# BAKER

## LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>SIT-DOWN RIDER</b>								
B25TE 33.50 x 19.75 x 25.50	24	850	12-85-21	32.63	19.25	22.63	N/A	12-875C
B30TE 32.75 x 20.10 x 25.82	24	850	12-85-21	32.63	19.25	22.63	N/A	12-875C

ABOVE REQUIRES: YC7204 CONN., POSITION-C, 24" LEAD LENGTH, W/O COVER

<b>SIT-DOWN RIDER</b>								
B30CE 39.10 x 18.80 x 31.20	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
	48	625	24-125-11	37.75	18.00	30.38	24-600B	24-600C
B30/35SC 38.75 x 18.88 x 32.00	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
B30TE/S 32.67 x 29.29 x 25.82	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	36	765	18-85-19	32.00	28.00	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
OPTIONAL B35SC 38.75 x 21.25 x 32.00	36	875	18-125-17	38.50	20.13	30.38	N/A	18-875C
<b>SIT-DOWN RIDER</b>								
B40CE/BFE40 39.10 x 21.50 x 31.20	36	875	18-125-17	38.50	20.13	30.38	N/A	18-875C
	48	750	24-125-13	38.13	21.00	30.38	N/A	24-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>SIT-DOWN RIDER</b>								
B40/50/60TE 40.94 x 34.69 x 31.00	72	750	36-125-13	38.13	31.00	30.38	N/A	36-725D

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

<b>SIT-DOWN RIDER</b>								
STANDARD COMP. B50/70/80CE/BFE50	36	1125	18-125-19	38.50	22.38	30.38	N/A	18-1050C
OPTIONAL COMP. B60CE/BFE60	48	875	24-125-15	38.50	23.63	30.38	N/A	24-875C
STANDARD COMP. B60CE/BFE60 OPTIONAL B70CE 39.10 x 24.80 x 31.20	36	1375	18-125-23	38.50	27.25	30.38	N/A	18-1450C
	48	1000	24-125-17	38.50	27.00	30.38	N/A	24-1050C
	48	1125	24-125-19	38.50	29.75	30.38	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 24" LEAD LENGTH, W/O COVER

<b>SIT-DOWN RIDER</b>								
TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
B80CE/BFE80 39.10 x 35.20 x 31.20	36	1750	18-125-29					
	48	1250	24-125-21	38.50	33.00	30.38	N/A	24-1200C
BTE/S35 32.67 x 28.30 x 25.82	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
	48	510	24-85-13	32.00	25.88	22.63	24-450B	24-450C
BTE30 32.67 x 20.10 x 26.80	24	900	12-100-19	29.88	19.13	25.63	N/A	12-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>NARROW AISLE REACH TRUCK</b>								
BOP30 36.50 x 14.63 x 31.50	24	750	12-125-13	35.88	11.75	30.38	12-725B	12-725C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

<b>NARROW AISLE REACH TRUCK</b>								
BRT35/BST40 39.50 x 14.60 x 31.80	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
OPTIONAL COMP. 39.50 x 16.60 x 31.80	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
BRT30D/BRT45 38.30 x 16.60 x 31.80	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL BRT30D/45 38.30 x 21.20 x 31.80	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 24" LEAD LENGTH, W/O COVER

<b>ORDER SELECTOR</b>								
BOS15 37.00 x 14.60 x 31.50	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>STAND-UP RIDER</b>								
BSC35 39.25 x 21.25 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 24" LEAD LENGTH, W/O COVER

<b>HAND TRUCK</b>								
BW30/BW40FL 27.40 x 9.25 x 26.20	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A

ABOVE REQUIRES: SBX175 GREY CONN., POSITION-B, 21" LEAD LENGTH (18" FOR BW40FL), W/COVER

<b>WALKIE RIDER</b>								
BW & WR40/60/80	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
PALW & WR60/80	12	600	12-100-13	30.88	7.75	26.25	6-600B	6-600C
31.50 x 8.25 x OPEN	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
BW50 26.5 x 9.20 x OPEN	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	375	12-125-7	25.50	8.63	31.00	12-380B	N/A
STANDARD BW60/80 OPTIONALBWR40/60 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

CBR2500 36.88 x 13.50 x 31.00	24	875	12-125-15	35.25	13.00	31.00	N/A	12-875C
----------------------------------	----	-----	-----------	-------	-------	-------	-----	---------

ABOVE REQUIRES: 175 GREY CONN., POSITION-D, 20" LEAD LENGTH, W/COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
CBR3000/4000 36.88 x 14.62 x 31.00	24	875	12-125-15	35.25	13.00	31.00	N/A	12-875C
CBW2500/3000/4000 32.62 x 14.62 x 23.25	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-D, 20" LEAD LENGTH, W/COVER

CBR30 38.75 x 16.50 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
--------------------------------	----	-----	-----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: EC5810 CONN., POSITION-B, 21" LEAD LENGTH, W/O COVER

THREE/FOUR WHEEL TRUCK								
E15 32.67 x 20.10 x 25.50	24	765	12-85-19	29.88	19.25	22.63	12-725B	12-725C
	24	850	12-85-21	32.63	19.25	22.63	N/A	12-875C
E15C 32.75 x 21.00 x 30.75	48	340	24-85-9	31.88	18.13	22.63	24-380B	24-380C
E15S 32.67 x 29.29 x 25.82	36	765	18-85-19	32.25	29.00	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
E16 32.67 x 28.30 x 25.82	36	680	18-85-17	32.25	26.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>FOUR WHEEL TRUCK</b>								
E20B 39.10 x 21.50 x 31.20	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C
	48	750	24-125-13	38.13	21.00	30.38	N/A	24-725C
E25B 39.10 x 24.80 x 31.20	36	1125	18-125-19	38.50	22.38	30.38	N/A	18-1050C
	48	875	24-125-15	38.50	23.63	30.38	N/A	24-875C
E30B 39.10 x 30.30 x 31.20	36	1375	18-125-23	38.50	27.25	30.38	N/A	18-1450C
	48	1000	24-125-17	38.50	27.00	30.38	N/A	24-1050C
E40B 39.10 x 33.20 x 31.20	36	1375	18-125-23	38.50	27.25	30.38	N/A	18-1450C
	48	1250	24-125-21	38.50	33.00	30.38	N/A	24-1200C

ABOVE REQUIRES: 350 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

EFR 36.50 x 12.13 x 31.00	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
	24	600	12-150-9	35.38	10.88	31.00	12-600B	12-600C
OPTIONAL COMP. 36.50 x 14.62 x 31.00 36.50 x 16.62 x 31.00	24	875	12-125-15	35.25	13.00	31.00	N/A	12-875C
	24	850	12-170-11	35.38	13.13	31.00	N/A	12-875C
	24	1020	12-170-13	35.38	15.50	31.00	N/A	12-1050C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

EFR30/40/60 38.50 x 12.12 x 32.00	24	750	12-125-13	35.88	11.75	30.38	12-725B	12-725C
	24	600	12-150-9	35.38	10.88	30.38	12-600B	12-600C

ABOVE REQUIRES: EC5810 CONN., POSITION-B, 21" LEAD LENGTH, W/O COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
OPTIONAL COMP. EFR30/40/60  38.50 x 14.62 x 32.00	24	875	12-125-15	36.13	14.25	30.38	N/A	12-875C
	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	24	850	12-170-11	36.25	14.25	30.38	N/A	12-875C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL COMP.  38.50 x 16.62 x 32.00	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1050C
	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: EC5810 CONN., POSITION-B, 21" LEAD LENGTH, W/O COVER

EFW  31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

EFW30/40/60  36.50 x 8.25 x 32.00	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
	24	255	12-85-7	33.88	7.75	23.25	12-255A/B	N/A
OPTIONAL COMP.  36.50 x 12.12 x 32.00	12	510	6-85-13	29.00	11.00	23.25	6-450A/B	6-450C
	12	750	6-125-13	29.88	11.00	31.00	6-725B	6-725C
	24	510	12-85-13	35.88	11.75	23.25	12-450B	12-450C
	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
OPTIONAL COMP.  36.50 x 13.50 x 32.00	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	24	875	12-125-15	35.25	13.00	31.00	N/A	12-875C
	24	600	12-150-9	35.38	10.88	31.00	12-600B	12-600C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 21" LEAD LENGTH, W/COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>PALLET TRUCK</b>								
EGU20 26.00 x 9.00 x 26.00	24	255	12-85-7	25.50	8.63	22.63	12-255A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER

FTA030, FTD020/025 32.88 x 28.81 x 23.00	36 48	680 510	18-85-17 24-85-13	32.25 31.00	26.75 25.75	22.63 22.63	18-725B 24-450B	18-725C 24-450C
FTD030/040 39.50 x 27.88 x 23.62	36 48	935 680	18-85-23 24-85-17	38.50 38.50	26.75 27.00	22.63 22.63	N/A N/A	18-875C 24-725C
OPTIONAL FTD030/040 STANDARD FTD050 39.50 x 30.88 x 23.62	36 48	1020 765	18-85-25 24-85-19	38.50 38.50	29.13 29.75	22.63 22.63	N/A N/A	18-1050C 24-725C
OPTIONAL FTD040/050 STANDARD FTD055 39.50 x 33.88 x 23.62	36 48	1105 850	18-85-27 24-85-21	38.50 38.50	31.38 33.00	22.63 22.63	N/A N/A	18-1050C 24-875C
FTD060/070/080 39.50 x 36.94 x 24.00	36 48	1275 935	18-85-31 24-85-23	38.50 38.50	36.38 36.00	22.63 22.63	N/A N/A	18-1200C 24-875C
FTD100/110 46.94 x 40.00 x 23.90	36 48	1360 1105	18-85-33 24-85-27	38.50 42.00	38.13 38.50	22.63 22.63	N/A N/A	18-1450C 24-1050C
FTD400 39.50 x 27.88 x 23.62	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C

ABOVE REQUIRES: EC5810 CONN., POSITION-A, 30" LEAD LENGTH, W/O COVER



**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
GAW/GAWR 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	12-450B	12-450C
	12	750	6-125-13	30.88	7.75	31.00	12-725B	12-725C
OPTIONAL COMP. 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
MTW/MTPW 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. MTR/MTW/MTPW STANDARD MTR 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	23.25	12-725B	12-725C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

MTPR 33.00 x 12.13 x 31.00	24	625	12-125-11	32.25	11.13	31.00	12-600B	12-600C
-------------------------------	----	-----	-----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

PALAR 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 20" LEAD LENGTH (OPT.COMP.20"), W/COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
PALR 33.00 x 12.13 x 31.00	24	625	12-125-11	32.25	11.13	31.00	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

<i>WALKIE RIDER</i>								
PALRT/PALW 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

<i>WALKIE RIDER</i>								
PALW30/301 29.50 x 7.56 x 25.31	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

<i>WALKIE RIDER</i>								
PALWSC/WSS/WR 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
OPTIONAL COMP. PALWR60/80 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
PALWR4WE35 36.00 x 8.25 x 31.50	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 36.00 x 11.50 x 31.50	24	425	12-85-11	32.25	11.13	23.25	12-450B	12-450C
	24	750	12-125-11	32.25	11.13	31.00	12-725B	12-725C
OPTIONAL PPTW STANDARD PPRT 31.50 x 13.50 x OPEN	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
<b>WALKIE RIDER</b>								
PPTW 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450A/B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

<b>NARROW AISLE REACH TRUCK</b>								
R14 40.63 x 17.32 x 30.87	48	400	24-100-9	38.50	14.63	25.63	24-380B	24-380C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 24" LEAD LENGTH, W/O COVER

RRTSO 36.88 x 12.33 x 31.00	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
--------------------------------	----	-----	-----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

RTP 36.88 x 12.50 x 31.00	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
------------------------------	----	-----	-----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: EC5810 CONN., POSITION-B, 21" LEAD LENGTH, W/COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SCBHR30 36.62 x 14.62 x 26.25	24	595	12-85-15	35.38	13.00	23.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 21" LEAD LENGTH, W/COVER

XTENDRD25/30D/35D XTENDR040/45D 36.50 x 12.13 x 31.00	24 24	750 600	12-125-13 12-150-9	35.88 35.38	11.75 10.88	30.38 30.38	12-725B 12-600B	12-725C 12-600C
OPTIONAL COMP. 36.50 x 14.62 x 31.00 36.50 x 16.62 x 31.00	24 24 24	850 875 1020	12-170-11 12-125-15 12-170-13	35.38 35.25 35.38	13.13 13.00 15.50	30.38 30.38 30.38	12-875B 12-875B N/A	12-875C 12-875C 12-1050C
OPTIONAL COMP. 38.75 x 12.13 x 31.00 38.75 x 14.62 x 31.00 38.75 x 16.62 x 31.00	36 36 36	500 625 750	18-125-9 18-125-11 18-125-13	38.00 38.00 38.00	11.00 13.25 15.50	30.38 30.38 30.38	18-450B 18-600B 18-725B	18-450C 18-600C 18-725C
OPTIONAL COMP. XTENDR30D 38.50 x 14.62 x 32.00 38.50 x 16.62 x 32.00	24 24 24	1000 960 1125	12-125-17 12-170-13 12-125-19	38.25 35.38 38.38	13.50 15.50 15.00	30.38 30.38 30.38	N/A 12-875B N/A	12-1050C 12-875C 12-1200C
OPTIONAL COMP. XTENDR35 38.50 x 12.12 x 32.00	24	750	12-125-13	35.88	11.75	30.38	12-725B	12-725C
OPTIONAL COMP. 38.50 x 14.62 x 32.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

**BAKER TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
XTENDR45/60 38.50 x 14.62 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
OPTIONAL COMP. XTENDR35/45/60 38.50 x 16.62 x 32.00	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

XTENDW 31.50 x 8.25 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 31.50 x 13.50 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: YC7204 CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

XTENDW30 36.00 x 8.25 x 32.00	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. XTENDW25/30/40 36.00 x 12.12 x 32.00	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
	24	600	12-150-9	35.38	10.88	31.00	12-600B	12-600C
OPTIONAL COMP. XTENDW25/30/45 36.00 x 14.62 x 32.00	24	875	12-125-15	35.25	13.00	31.00	12-875B	12-875C
	24	850	12-170-11	35.38	13.13	31.00	12-875B	12-875C

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 18" LEAD LENGTH, W/COVER

**Jun-98**