

KALMAR

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ACE60/70 41.00 x 32.50 x 23.50	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C
ACE80/100 39.75 x 35.12 x 23.60	36	1190	18-85-29	38.50	33.63	22.63	N/A	18-1200C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
ACE120 39.75 x 40.60 x 23.50	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C

ABOVE REQUIRES: 350 GREY CONN., 30" LEAD LENGTH, W/O COVER

NARROW AISLE

ACNR25/30/40D, ACNS30/40S 38.50 x 15.06 x 32.60	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
---	----	------	-----------	-------	-------	-------	-----	----------

ABOVE REQUIRES: 350 RED CONN., 12" LEAD LENGTH, W/O COVER,

NARROW AISLE

ACNR30/40C, ACNS30/40 38.50 x 16.63 x 32.60	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
--	----	-----	-----------	-------	-------	-------	---------	---------

ABOVE REQUIRE: 350 GREY CONN., 12" LEAD LENGTH, W/O COVER

HAND TRUCK

ACWA40/60, ACNB40/60, ACWF40/60, ACWT 32.00 x 8.13 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRE: 350 GREY CONN., 12" LEAD LENGTH, W/COVER

KALMAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
E40B 39.25 x 28.25 x 23.50	36 48	935 680	18-85-23 24-85-17	38.50 38.50	26.75 27.00	22.63 22.63	N/A 24-725B	18-875C 24-725C
E50B 39.25 x 31.25 x 23.50	36 48	1020 765	18-85-25 24-85-19	38.50 38.50	29.13 29.75	22.63 22.63	N/A 24-725B	18-1050C 24-725C
E60B 39.25 x 34.25 x 23.50	36 48	1105 850	18-85-27 24-85-21	38.50 38.50	31.38 33.00	22.63 22.63	N/A N/A	18-1050C 24-875C

ABOVE REQUIRE: 350 GREY CONN.(36v), BLUE (48v), 18" LEAD LENGTH, W/O COVER

STAND UP RIDER

ED30 38.50 x 14.00 x 24.50	36	425	18-85-11	38.38	13.31	22.63	18-450B	18-450C
-------------------------------	----	-----	----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: 350 GREY CONN., 18" LEAD LENGTH, W/O COVER

SIT DOWN RIDER

ED25/30 32.58 x 26.25 x 23.25	36 48	595 510	18-85-15 24-85-13	31.75 31.00	24.00 25.75	22.63 22.63	18-600B 24-450B	18-600C 24-450C
----------------------------------	----------	------------	----------------------	----------------	----------------	----------------	--------------------	--------------------

ABOVE REQUIRES: 350 GREY CONN., 30" LEAD LENGTH, W/O COVER

ESP20 36.00 x 13.50 x OPEN	24 24 24	595 700 875	12-85-15 12-100-15 12-125-15	35.38 35.38 35.25	13.00 12.88 13.00	23.25 26.25 31.00	12-600B 12-725B N/A	12-600C 12-725C 12-875C
ESP20/30 36.00 x 13.50 x OPEN	24 24 24	595 700 875	12-85-15 12-100-15 12-125-15	35.38 35.38 35.25	13.00 12.88 13.00	23.25 26.25 31.00	12-600B 12-725B N/A	12-600C 12-725C 12-875C

ABOVE REQUIRES: 175 GREY, 18" LEAD LENGTH, W/COVER

KALMAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ET30 39.00 x 20.25 x 23.25	24	1020	12-85-25	38.88	19.31	22.63	N/A	12-1050C

ABOVE REQUIRES: 350 GREY CONN., 18" LEAD LENGTH, W/O COVER

ELECTRIC DOUBLE REACH TRUCK								
ND30B 38.75 x 16.40 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 20.90 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC DOUBLE REACH TRUCK								
NR35B 38.75 x 16.40 x 32.00	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 14.40 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN. (36v), RED (24v), POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC DOUBLE REACH TRUCK								
NR45B 38.75 x 16.40 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 20.90 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

KALMAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELECTRIC STRADDLE TRUCK								
NS40B 38.75 x 16.40 x 32.00	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 14.40 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN (36v), RED (24v), POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC STRADDLE TRUCK								
NS50B 38.75 x 16.40 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C
OPTIONAL COMP. 38.75 x 20.90 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC WALKIE HIGH LIFT, COUNTERBALANCED STACKER, END CONTROL								
ELECTRIC WALKIE HIGH LIFT, STRADDLE REACH, END CONTROL								
WC30/40, WR30 32.30 x 13.30 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

ELECTRIC WALKIE HIGH LIFT, STRADDLE STACKER, END CONTROL								
WS30/40 32.30 x 13.30 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

KALMAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELECTRIC WALKIE HIGH LIFT, STRADDLE STACKER, END CONTROL								
WSI20/25 27.375 x 9.00 x OPEN	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	25.50	8.69	26.25	12-255A/B	N/A

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

Jun-98