

# SCHAEFF

## LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
<b>SIT DOWN RIDER</b>								
SD-2020E/2024E 27.00 x 19.50 x 23.00	36	425	18-85-11	26.38	19.13	22.63	18-450B	18-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-A, 18" LEAD LENGTH, W/O COVER

<b>STAND UP RIDER</b>								
SLC-2020E/LC2024E SLC2524E 27.00 x 19.50 x 23.00	36	425	18-85-11	26.38	19.13	22.63	18-450B	18-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

<b>STAND UP COUNTERBALANCE RIDER</b>								
W20/25 38.75 x 15.50 x 31.50	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
W30/35 38.75 x 16.12 x 31.50	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
W33/38 38.81 x 18.12 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
W40/45/50/55/60 38.88 x 20.75 x 31.50	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-D, 9" LEAD LENGTH, W/O COVER

**SCHAEFF TRUCKS CONTINUED...**

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
STAND UP COUNTERBALANCE TURRET RIDER								
W90t 38.88 x 20.75 x 31.50	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-D, 9" LEAD LENGTH, W/O COVER

**Jun-98**