

TAYLOR-DUNN

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
C4-10 35.50 x 19.75 x 23.00	36	425	18-85-11	31.88	17.75	22.63	18-450B	18-450C
	36	510	18-85-13	30.88	19.25	22.63	18-450B	18-450C
C4-20 43.50 x 19.75 x 23.00	36	595	18-85-15	38.50	17.75	22.63	18-600B	18-600C

ABOVE REQUIRES: SBX-175 CONNECTOR

C4-25 32.00 x 16.50 x 24.00	48	255	24-85-7	31.25	14.75	22.63	24-255B	N/A
OPTIONAL 32.00 x 16.50 x 24.00	24	510	12-85-13	30.88	12.88	23.25	12-450B	12-450C
	36							

E4-51 30.50 x 13.38 x 24.00	24	510	12-85-13	30.88	12.88	23.25	12-450B	12-450C
E4-57 30.50 x 26.38 x 24.00	36	595	18-85-15	29.75	25.50	22.63	18-600B	18-600C

ABOVE REQUIRES: 175 CONNECTOR

P2-50 39.50 x 32.50 x 22.63	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
--------------------------------	----	------	----------	-------	-------	-------	-----	----------

ABOVE REQUIRES: EC 5816B CONNECTOR

Aug-98